

CLAIMS

What is claimed is:

1. An ice axe device, comprising:
 - a) an elongated shaft with opposite proximal and distal ends;
 - 5 b) a pick, disposed at the distal end of the elongated shaft;
 - c) a grip, disposed at the proximal end of the elongated shaft; and
 - d) a pommel, adjustably securable to a proximal end of the grip, movable
towards and away from the grip to respectively shorten and lengthen a length of the
grip.
- 10 2. A device in accordance with claim 1, further comprising:
 at least one spacer, selectively disposable on the grip, to selectively lengthen
the length of the grip.
- 15 3. A device in accordance with claim 2, wherein the at least one spacer is selectively
disposable between the grip and the pommel.
4. A device in accordance with claim 2, further comprising:
 - a protrusion, formed on the proximal end of the grip, to receive the at least one
20 spacer thereon; and
 - a bore, extending through the at least one spacer to receive the protrusion of
the grip therethrough.
5. A device in accordance with claim 1, wherein the grip is a primary grip, and
25 further comprising:
 - a secondary grip, disposed at the proximal end of the elongated shaft between
the proximal end of the shaft and the primary grip; and
 - the primary grip being off-set from the secondary grip.
- 30 6. A device in accordance with claim 5, further comprising:
 - an attachment arm, extending rearwardly from the proximal end of the
secondary grip to a distal end of the primary grip.

7. A device in accordance with claim 1, further comprising:

a cavity, formed in the pommel;

a protrusion, formed on the proximal end of the grip and extendable into the cavity of the pommel; and

5 means for securing the protrusion in the cavity.

8. An ice axe device, comprising:

a) an elongated shaft with opposite proximal and distal ends;

b) a pick, disposed at the distal end of the elongated shaft;

10 c) a secondary grip, disposed at the proximal end of the elongated shaft;

d) a primary grip, disposed at a proximal end of the secondary grip; and

e) a pommel, adjustably securable to a proximal end of the primary grip, movable towards and away from the primary grip to respectively shorten and lengthen a length of the primary grip.

15

9. A device in accordance with claim 8, further comprising:

at least one spacer, selectively disposable on the primary grip, to selectively lengthen the length of the primary grip.

20 10. A device in accordance with claim 9, wherein the at least one spacer is selectively disposable between the primary grip and the pommel.

11. A device in accordance with claim 9, further comprising:

25 a protrusion, formed on the proximal end of the primary grip, to receive the at least one spacer thereon; and

a bore, extending through the at least one spacer to receive the protrusion of the primary grip therethrough.

30 12. A device in accordance with claim 8, wherein the primary and secondary grips are off-set from one another.

13. A device in accordance with claim 8, further comprising:

a cavity, formed in the pommel;